

产品一览表

PLE系列

部件表	温度特性	静电容量(pF)	静电容量公差	使用温度范围	额定电压(Vdc)	绝缘阻抗 (MΩ min.)
PLE123	SL	10	±1pF	-25~+85°C	50	5,000
PLE123	SL	22	±20%	-25~+85°C	50	5,000
PLE123	YE	220	+100,-0%	-25~+85°C	50	5,000
PLE123	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE12	SL	1	±1pF	-25~+85°C	50	5,000
PLE12	SL	10	±1pF	-25~+85°C	50	5,000
PLE12	YE	470	+100,-0%	-25~+85°C	50	5,000
PLE12	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE22	SL	5	±1pF	-25~+85°C	50	5,000
PLE22	SL	22	±20%	-25~+85°C	50	5,000
PLE22	YN	47	±20%	-25~+85°C	50	5,000
PLE22	YN	100	±20%	-25~+85°C	50	5,000
PLE22	YE	470	±20%	-25~+85°C	50	5,000
PLE22	YF	1,000	+100,-0%	-25~+85°C	50	5,000
PLE22	YF	2,000	+100,-0%	-25~+85°C	50	5,000
PLE32	X7R	1,200	±20%	-55~+125°C	50	5,000
PLE32	YF	3,000	+80,-20%	-25~+85°C	50	5,000
PLE255	X7R	1,000	+100,-0%	-55~+125°C	50	5,000
PLE255	YF	4,700	+80,-20%	-25~+85°C	50	5,000
PLE23	SL	2	±1pF	-25~+85°C	50	5,000
PLE23	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE23	YF	2,000	+100,-0%	-25~+85°C	50	5,000
PLE33	SL	100	±20%	-25~+85°C	50	5,000
PLE33	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE33	YF	2,200	+100,-0%	-25~+85°C	50	5,000
PLE335	YE	1,000	+100,-0%	-25~+85°C	50	5,000
PLE335	YF	2,000	+100,-0%	-25~+85°C	50	5,000

上述表中没有显示的形状、静电容量值的产品可能没有尽录，详细资料请联系我司营业部。